

GH PLANT



BRITAIN'S LEADING
TRAILER MANUFACTURER

GH64

This is the smallest of the GH plant trailer range. With a bed size of 1.88m x 1.23m (6' x 4') and a payload of 1230kg (gross weight 1500kg), the GH64 is designed for smaller items of plant such as micro-excavators.

Compact yet robust, this is a neat and convenient single axle trailer that can be towed behind a car.

As with all GH models, its galvanized welded construction and leaf spring suspension ensures it will withstand tough conditions.

GH64 model is available with two ramp options, a 1.2m (3'9") ramp with mesh infill or a longer 1.45m (4'9") bevelled ramp with no infill.

GH94 & GH94BT

The GH94 comes in two versions – most popular is a beavertailed version on 165R13C tyres – known as GH94BT. Also available is a GH94 with a flat bed on 195/55R10C tyres. The Beavertail feature means that the excellent loading angle of 13° is maintained during loading.

The GH94 and GH94BT are extremely versatile plant trailers. A 24mm thick platform makes them particularly suitable for transporting a wide selection of plant, including tracked excavators, and many items of wheeled equipment such as rollers and a variety of access platforms.



GH64 1.45m (4'9") bevelled ramp



GH94 with 195/55R10C tyres and 1.2m (3'9") full width ramp and optional 12/24v LED lights



An LED 12/24v option is available on all GH models. This can be a real benefit on hire fleets. However, LED lights draw very little current and this means some vehicles present problems when coupled with LED equipped trailers, including (but not limited to) hazard warning lights flashing continuously and erroneous dashboard tell-tale lights. Where such problems occur, these are vehicle problems and Ifor Williams Trailers will not be responsible for their resolution. Owners are strongly advised to make thorough checks with the vehicle manufacturer before buying an LED equipped trailer.

GH94BT with 1.45m (4'9") skids

Some access platforms e.g. electric scissor lifts present particular transport challenges due to their narrow width, low ground clearance and high-point load wheels with low friction. The GH trailers with their thick floor and low loading angle are one of the few trailers generally suitable for carrying such plant.



GH1054 with 1.2m (3'9") full width ramp and optional 12/24v LED lights



GH94 & GH94BT

cont. . .

The 2.79m (9') length of the GH94 and GH94BT provides ample loading space behind the rear axle. This enables a full range of mini-excavators to be loaded along with machines with a more central centre of gravity, such as hi-tip dumpers.

All GH94 models are available with a patented breaker storage option. Further details can be found overleaf.

GH1054

The GH1054 is only available with a beavertailed feature and offers one of the highest payloads ever produced by Ifor Williams Trailers. With its robust, welded construction and heavily treaded 185/70R13C tyres, the GH1054 is a rugged trailer for demanding conditions.

A 24mm platform makes the GH1054 particularly suitable for transporting a wide selection of plant, including tracked excavators, and many items of wheeled equipment such as rollers and a variety of access platforms.

Ramp Options

Three self-supporting knife-edge options are available on the GH range.

- The 1.2m (3'9") full width ramp provides the benefits of a full width ramp and is bevelled to help guide the tracks or wheels of plant being loaded.
- The 1.45m (4'9") bevelled ramp offers a reduced loading angle of 13° during loading and the ramp is bevelled to help guide the tracks or wheels of plant being loaded.
- The 1.45m (4'9") sliding skids offers all the benefits of the 1.45m bevelled ramp with further flexibility for easier loading of narrower plant e.g. access platforms.

In addition a fourth option, comprising of 1.2m (3'9") sliding skids is available for the GH1054 only. This version offers maximum payload.

Features & Options

Standard features on all models include, walk-on steel treadplate mudguards, spring assisted ramp*** with integrated ramp supports, bucket rest, heavy duty jockey wheel and five pairs of 500kg lashing points per trailer.

Coupling eye options are also available as an alternative to the standard coupling fitted to the trailer.

***Not on Sliding Skids



Breaker Box

Available on most models, the breaker storage is designed to suit an Atlas Copco SB102 hydraulic breaker. This enables secure storage and transportation of the breaker whether attached to or detached from the excavator boom. Breaker Storage combines as a bucket rest when breaker is not attached. Contact your local distributor for more information.

Standard Bucket Rest

Raised bucket rest with lip for excavator teeth.

Winch & Bracket

1050kg Manual Winch with Bracket. Attached to the bucket rest, the winch provides loading assistance to lighter items of plant that cannot be driven onto the trailer.

Steel Toolbox

The heavy duty, lockable, steel toolbox allows three sets of 8m ratchet straps to be carried. (Padlock not included).

Specifications

	Tyres	Gross Weight	Payload	Interior Width	Interior Length	1.2m (3'9") full width ramp #	Trailer with 1.45m (4'9") bevelled ramp (no infill)	Trailer with 1.45m (4'9") sliding skids	Heavy Duty Jockey Wheel	Five Pairs of Lashing Points	Three pairs of Extra Lashing Points	12/24v LED Lights†	Spare Wheel & Bracket	Heavy Duty Lockable Steel Toolbox	Aluminium Treadplate Floor Covering	4500lb (2040kg) Electric Winch, Battery & Bracket	1050kg Manual Winch Kit	Breaker Box**
GH64	195/55R10C	1500kg	1230kg*	1230mm / 4'	1880mm / 6'1"	Option	Option	Option	Std	Std	Option	Option	Std	-	Option	-	Option	-
GH94	195/55R10C	2700kg	2195kg	1310mm / 4'3"	2795mm / 9'1"	Option	Option	Option	Std	Std	Option	Option	Option	-	Option	Option	Option	Option
GH94BT	165R13C	2700kg	2165kg	1310mm / 4'3"	2795mm / 9'1"	Option	Option	Option	Std	Std	Option	Option	Option	Option	Option	Option	Option	Option
GH1054	185/70R13C	3500kg	2835kg	1626mm / 5'4"	3045mm / 9'11"	Option	Option	Option	Std	Std	Option	Option	Option	Option	Option	Option	Option	Option
GH106	185/70R13C	3500kg	2790kg	1840mm / 6'	3045mm / 9'11"	Option	Option	Option	Std	Std	Option	Option	Option	Option	Option	-	-	-
GH126	185/70R13C	3500kg	2735kg	1840mm / 6'	3660mm / 12'	Option	Option	Option	Std	Std	Option	Option	Option	Option	Option	-	-	-
GH146 Tri-Axle	185/70R13C	3500kg	2560kg	1840mm / 6'	4285mm / 14'	Option	Option	Option	Std	Std	Option	Option	Option	-	Option	-	-	-

All Ifor Williams braked trailers come as standard with a 13 pin towing electric plug. This is in order to comply with the requirement under ECWVTA regulations to provide trailer reversing lights.

* Payload includes weight of spare wheel. ** Designed for Atlas Copco SB102 Hydraulic Breaker. † See page 3 for important safety factors regarding LED Lights. # 1.2m (3'9") ramp with mesh infill on GH64.

